

# Centerm

## C71



Golden distributor  
of Centerm

### PROFILE

Centerm C71 is a specialized zero client for PCoIP solution, through which you can achieve unified management of high-end graphics workstation designed to render 3D graphic solutions with the PCoIP host card.

### FEATURES

➤ **Specialized zero client for PCoIP solution**

C71 has excellent performance in 3D graphics, which remedies the shortcomings of CITRIX and RDP solution in 3D applications.

➤ **High Performance**

Support 2500x1600 super high resolution (single display) based on the high performance graphic engine and pixel processing core.

➤ **High Security**

All computing and storage hardware are protected in security center, only pixels are transmitted to each C71 and all data are still stored securely in data center.

➤ **Zero Maintenance**

No CPU, no operating system, no storage, no fan, no noise, no need to upgrade the firmware or virus database frequently.

➤ **Low TCO solution**


Low price, low power consumption and no maintenance guarantee the low TCO.



### Connectivity



VESA Mounting



Website: [www.thinava.com](http://www.thinava.com)

E-mail: [info@thinava.com](mailto:info@thinava.com)

## SPECIFICATION

SYSTEM	
Processor	Teradici PCoIP zero client
Available Operating System	N/A
Management	PCoIP Management Console
MEMORY	
RAM (DDR3)	Onboard 512MB
DISPLAY	
Port	1x DVI-I port (1 VGA adapter included), 1x DVI-D Port
Resolution	1920 x 1200 @ 60Hz
Color Depth	Up to 24bits true color
Dual Display	Supported
Network	
LAN	x1 (10/100/1000 Base-T Fast Ethernet, RJ-45)
I/O PERIPHERAL INTERFACE	
USB 2.0	x3 (rear), x1 (front)
RJ-45	x 1
AUDIO	
Ports	Front: Line-out x 1 , Mic-in x 1, (1/8-inch mini jack)
DIMENSION	
Device (H x W x D), upright	131mm x 31.5mm x 167mm
Packaging	294mm×188mm×67mm
Net Weight	0.55 kg
Power	
Adapter	Worldwide auto-sensing 100-240V AC, 50/60 Hz, 12V/3A DC
Power Consumption	6.5w
Mounting	
VESA Bracket	VESA Mounting Kit (optional)
Kensington Lock	Built-in Kensington Lock Slot
ENVIRONMENT	
Cooling	Fan-less Convection
Operation Temperature	0°C to 40°C
Relative Humidity	30% to 90% non-condensing